

SM LIGHTS



BEAM 5R. 7R. 10R. 15R. 20R
PAR LED 3x72w. 3x54w. 3x36w

20-R



Voltage: AC110–240V 50-60HZ

Power: 600W

Voltage protect : PFC power factor compensation, even in the case of voltage fluctuations ($\pm 10V$) environments also can be used.

Ballast: electric ballast and AC/DC power supply.

Lamp : A17R-350W / OSRAM SIRIUS HRI 330W

Color temperature : 11000K

CH : 20-standard Channel , Master-Slave , Automatic.

Light size : 385×420×590 (mm) N.W : 18KG

Single flightcase size : 485×455×770 (mm)

N.W : 20KG

15-R



Voltage: AC90V-240V 50-60HZ

Lamp: 16R 330W

Power: 400W

Lifetime: 500 Hours

Color temperature: 6000K

Color wheel: One color wheel 14 Colors + white, with IRIS function.

Gobo wheel: 1 rotating patterns, 7 gobos + white

One rotation 16 prism. (can be customized 8 prism). Can reverse the direction of rotation and have a prism positioning. A fixed 24 prism.

Focus, with touch rotation LED screen, Optics, Combination of an optical lens. Group zoom 0-3.9 degrees, electronic focusing at 20 meters

Strobe shot and Strobe: strobe shoot fast action can be quickly interrupted beams, and can achieve 1-10 times per second strobe effect. With dimming effect

Zoom: Electronic linear zoom system.

Motor : By built-in microprocessor-controlled precision stepper motor components

Control: Microprocessor: high stability and strong anti-interference ability CPU

Number Control : DMX 512

Light body: molded by engineering plastic housing portfolio, streamline design, elegant appearance.

Fan: The DC12-24V fan and natural ventilation rate. Cooling fan and overheat protection Can adjust the speed of strobe

540° horizontal rotation of 270° vertical rotation, the two-step precision correct

Stand DMX512 Controller signal

16CH with LCD

Work place: Indoor, -20°C ~ 50°C

Housing: high-strength temperature plastic shell and metal powder coating technology, streamlined design.

Light size: 410mm×360mm×570mm

Packing size: 490mm×470mm×580mm

N.W: 21KG G.W: 24KG

10-R



Voltage : AC90V-240V 50Hz -60 Hz
 Power : 350W
 Lamp : 9R 280W
 Color Temperature : 6000°K
 Lifetime : 500hours
 Color : 1 color wheel, 14 colors + white, Continuous variable can be any color plate rotating direction of rainbow effect, one color wheel, each color wheel with 14 pcs color chip + white : Two gobo wheel, one fix wheel with 17 gobos + white, one rotation gobo wheel with 17 gobos + white, one rotation gobo wheel with 9 gobos (can change) + white to be a 3 prism (can rotation).
 Stroboscopic pat and strobe: fast Stroboscopic pat can Quickly interrupt beam, and can strobe 1-10 times / sec effect, also with dimming effect.
 Zoom : Electronic linear zoom system . dot matrix display, Four light touch switch, can reversible 180° display color wheel :
 Motor : Component by the built-in micro processor controlled precision stepper motor.
 Control : Microprocessor : Using high stability , strong anti-interference ability of the CPU
 Control : DMX512
 Light body : Combination by the engineering plastics shell, streamline design, Beautiful
 Fan : DC 12V Fan, Cooling
 Adjustable strobe frequency
 540° Level rotation , 270° Vertical rotation
 DMX512 control signal
 17CH, LCD display
 Working environment : Indoor , -20°C ~ 50°C
 Case : High-strength engineering temperature plastic shell and use metal powder spraying technology, streamline design.
 Size : 320x400x580mm
 N.W : 18.5kg

7-R 5-R



Voltage: 90V / 240V 50Hz * 60Hz
 Lamp: 7R MSD 200W 5R MSD 200W
 Power frequency: 250W Control channel: 16CH
 Color: 5600-8000K
 Function: a color wheel . 14 colors + white, a pattern plate .
 17 Pattern + white
 Replaceable pattern plate, high speed wobble effect, an atomizer, a eight prism, positive and negative direction of rotation
 And positioning function with prism. focus, zoom, LCD display.
 Optics: combined lens, zoom 0-3.9 degrees, electronic focusing on 20 meters
 Horizontal scanning: 540 degrees (16bit precision scanning)
 Vertical scanning: 280 degrees (16bit precision scanning)
 Size: 465mm * 380mm * 550mm
 N.W: 17KG
 G.W 19.8KG

SM 150W LED



Voltage: AC90-240V, 50-60Hz
 Power Consumption: 250W
 Lamp: 150w high power white
 LED Color plate: 7+white, can adjust speed with rainbow effect
 Fixed gobo plate: 6+white, slow to fast
 Rotating gobo plate: 6+white, double direction, speed adjustable, rotating
 Dimming/Strobe: dimming, 1-20times per sec
 Focus: electronic focus
 Pan: 540 degree,
 Tilt: 270 degree,
 Control mode : DMX512, master/slave, standalone
 Channel: 19CH
 Function: pan/tilt can adjust speed
 Casing: high-strength temperature plastic shell and aluminium alloy
 N.W: 15kg
 G.W: 17.8kg
 Product size: 400mm*360mm*560mm
 Packing size: 440mm*440mm*510mm

SM 60W LED



Voltage: AC220V
 Frequency: 50Hz
 Power: 120W
 LED: 60W high power led
 Color wheel: 7 colors+white, speed adjustable, with rainbow effect
 Fixed gobo wheel: 8gobos+white, gobos flow back and forth from slow to fast
 Rotating gobo wheel: 6gobos+white, reversible variable rotation
 Dimmer/strobe: dimming, 1-20 times/ sec
 Focus: electronic focus
 Focus: Pan 540° Tilt: 270°
 horizontal and vertical rotating speed adjustable
 Control mode: DMX512, 14CH
 Operation mode: stand-alone, master/slave, controller mode
 Housing: High temperature resistant engineering plastics+ aluminum alloy
 N.W: 7.5kg
 Product size: 360*260*420mm
 Packing size: 350*340*375mm

SM 60W LED BEAM



Control: DMX-512 11 channels
 Color wheel: 7 colors + white, spilt colors, rainbow effect
 Gobo wheel: 8 static gobos + white, rainbow effect, gobo shake
 Effect wheel: 3-facet prism (adjustable rotating speed and direction)
 Shutter: 0-20Hz
 Dimmer: Variable electronic dimmer (0-100%)
 Master/Slave activated by sound at pre-programmed function
 Pan: 540°/360°/180°, 8/16 bit movement resolution, automatic correction
 Tilt: 270°/180°/90°, 8/16 bit movement resolution, automatic correction
 Power supply: AC 110V-240V 60/50Hz
 Power consumption: 115W
 Light source: 60W white color LED
 Beam angle: 3°
 N.W.: 6.2Kg
 G.W.: 7.5Kg
 MEAS: 40CMx36CMx32CM

SM 30W LED



Voltage: AC90V~240V 50-60Hz
 Power: 80W
 Lamp: 30W LED white lamp
 Cooling system : Built-in convection heat transfer and air cooling
 Dimming: 0~100%
 Strobe: 0~20times/sec Many strobe effect
 Mode: DMX512/Master -Slave/Voice control
 Display: LCD display
 Channel: 12CH
 Scanning angle: Pan :540°, Tilt: 270°
 Can control the speed
 SWP VAR : 8/16bit
 Scanning location : The dislocation automatic recovery / electronic automatic positioning.
 Gobo wheel : 7 pattern, positive and negative rotate / can change gobo
 Color: 9 colors +white , Linear rainbow effect
 Size: 240*210*354mm
 G.W: 7Kg

SM 15W LED



Electrical Characteristics: AC90V-240V 50Hz-60Hz,
 Power : 30W
 Light Source: 15W LED lamp
 Operating modes: Voice / Automatic / DMX
 Control parameters: 13 or 5-channel selectable
 0 ~ 100% dimming, random strobe, RGB color mixing, pattern jitter effect.
 Horizontal / vertical rotation angle is optional, a variety of optional self-walking procedures and voice procedures
 Product parameters: 180*160*270mm(1 piece)
 Packing size: 460*285*290mm(2 pieces)
 N.W: 2.9kg
 G.W: 3.3kg(carton)

SM 10W LED



Voltage : AC110V-130V, 50-60HZ
 Lamp : LED 10W imported superbright
 Lamp white
 Control: DMX512, sound, auto-run, self-defined mode
 Function: 9/11CH, 0-100% linear dimming, manual focus, random strobe, multiple auto mode and sound control can be choose
 Color: 7+white
 Gobo: 8+white, fixed gobo plate
 Packing size: 200*200*200mm
 N.W: 2.2kg
 Suitable places: KTV, club, bar, dj club, show, party etc

SM 145W LED SUPER BEAM



Voltage: AC90v/240v, 50-60Hz
 Power consumption: 145W
 Lamp: 12pcs 10w RGBW 4-in-1 LED
 Channel: 18CH Dimmer: Linear dimmer
 Control: DMX, master- slave auto, sound-active
 Color: red, green, blue. white color mixed
 Function: New 7 colors beam ,flowers ,
 moremagic functions .The lights will work
 slow by automaticwithout signalspecial optical
 protect the light: Electronicaautomatic
 constant temperature system
 Horizontal : 540 degrees, fine-tuning 16bit
 200 degree , fine-tuning 16bit
 Size: 260*160*380mm
 Carton size: 520*340*500mm(2 pieces)
 N.W: 5.5kg G.W: 6.5kg

SM 119



Voltage: AC90-245V,50~60Hz
 Power: 75W
 Channels: 9/14CH
 Dimmer:LED display menu with invert
 Other feature: Compact and lightweight Easy to contro
 ILamp:LED 15W RGBWA 5-in-1
 Rated Lamp Life: 50,000hrs
 User modes:DMX512,Master /Stave, Auto Run,
 Stand alone,Sound active
 Head movement:Pan 540°,Tilt 270°
 ,User-selectable pan/tilt ranges
 Product color:Black
 Other feature: Compact and lightweight Easy to control
 Mains input:IECSize: 175 x 175 x245 mm
 Packing size: 240*225*290 mm
 N/G Weight: 4/5kg

SM 120



Voltage: AC110-240V, 50-60Hz
 Lamp: LED 3w*18pcs,R:6,G:6,B:6
 Channel mode: DMX512, fast auto-run ,
 slow auto-run, voice control
 Channel: 12CH
 Function: 0~100% dimming; random strobe;
 RGB mixed color; pan&tilt rotation, beam
 angle can choosable
 Suitable place: entertainment venues of ballroom,
 bar, stage, hotel, theater, KTV, concert...
 Packing size: 180*180*250mm
 N.G: 2.7kg

SM 118



Voltage: 110-240V
 Frequency: 50-60Hz
 Power: 70w
 Light source: LED RGBW 10W*7pcs
 Specs: 0-100% dimmer, strobe, Horizontal/Voice vertical rotation
 Angle is optional,
 many programs and optional voice control program is optional.
 Color: RGBW color mixed
 Channel: 10/13CH
 Channel mode: DMX/Voice / fast auto/slowly auto
 Function: Suitable for the entertainment venues of ballroom,
 bar, stage, hotel, theater, KTV, concert...
 G.W: 2.7Kg
 Size: 180*180*250mm

SM 068B



Voltage: AC90V-240V, 50/60Hz
 Consumption: 80W
 Fuse: 1A/250V
 LED lamp: 3W*18pcs powerful
 led each 6pcs
 Pan: 540°360°180° can be choose
 Tilt: 270°180°90° can be choose
 DMX control channel: 12 or 4CH
 Several strobe function can be choose,
 10 times dimming/sec
 RGB mixed, can mix many color
 Control function, master-slave control,
 DMX control, voice control
 LED display can be used in opposite side,
 open/close can be choose
 Fan can make cool
 Packing size: 180*180*250mm
 N/W: 2.7Kg

SM 096



Voltage: AC90V-240V, DC24V150W
 Lamp: 36pcs USA led import lamp
 Lifetime: 100000hours
 Lens: RGBW 4 colors (R8, G10, B10, W8)
 Mode: LED driven by constant current
 Control: DMX512, automatic, master-slave
 Channel mode: 8/10/15CH
 heat-dissipating mode: Use high thermal conductivity
 aluminum plate, aluminum heat conduction, fan cooled,
 overheating protection
 Horizontal/Vertical: X630°/Y240°
 Fast speed, quiet, can control speed
 Dimming: 0-100% line dimming
 Strobe: 1-25times/sec Display: LCD display
 Work place: indoor, -15~40°
 IP rate: Ip20 G.W: 4.9Kg
 Size: 250*150*290MM
 Packing Size: 310*210*365MM

SM 7x10W



Itage: AC90-240V
 Frequency: 50-60HZ
 Power: 120W
 Lamp: 7pcs high-brightness OSRAM 4-in-1 led
 Light angle: 8 degree
 Strobe: 1-20times/ sec
 Color: RGBW color mixed
 Channel: 15CH
 Control modes: DMX512, auto-run, sound, master-slave
 Packing size: 310*210* 370MM
 N.W: 3.3KG
 G.W: 5KG
 Suitable for the entertainment venues of ballroom, bar, stage, hotel, theater, KTV, concert...

SM 12x10W



Voltage: AC100V-240V 50-60Hz
 Power: 150w
 Led: 12PCS*10W RGBW 4IN1 CREE LED
 Lux: Lux4200 @ 5m
 DMX Channel: 9/12/14/16/28CH
 Beam angel: 20°
 Working modes: Auto, Sound, DMX, Master/Slave
 Control: DMX512, 3in/5in XLR base Master-slave, Sound, Auto
 Smooth electronic dimming: 0-100%
 Pan: 630 Tile: 200 speed adjustable
 Electronic strobe with pulse and random effects.
 High efficiency, low power consumption.
 Super compact, low weight.
 Dimension: 304*237*168mm
 Weight: 5.8kg

SM MATRIX 9x10W



Voltage: AC 110V-260V
 Frequency: 50-60HZ
 Power: 500w
 Lamp: 9*10w 4in1 led
 Channel: 15CH
 Control Mode: DMX512, master-slave, sound, auto-run
 Display: LCD display
 Rotating speed: 8/16 bit
 Effect can change: beam matrix moving head, beam only
 Beam angle: 7 degree
 Safe&Appearance: high strength and heat resistance plastic casing, streamlined appearance design
 Maximum temperature: 40 °C
 Packing size: 300*250*380mm
 G.W: 10kg

SM 36x10W



Voltage: AC 90~245V, 50~60Hz
 Lamp: 36*10W 4IN1 RGBW
 Rated Power :360W
 Control Singal: Dmx 512/Master-slave/Auto/Custom/Sound Control
 Channels: 14CH(RGBW/A) Installed with 36 LED Lamps, the power of the products reaches 360W. The average life time of each LED reaches 100, 000 hours. Low power consumption.
 Super luminance, comparable to the efficiency of halogen discharge lamps, rich and splendid color. DMX-512 control signal, 14 standard channels. The housing is made of streamline fashionable PC engineering Plastic Of after once casting. Wide range super tiny smooth scanning, horizontal scanning Angle reaches 540° , and vertical 270° , the scanning precision Reaches 8bit and 16bit, with smooth and precise positioning. Additionally, the scanning speed is adjustable. Infinite RGB color mixed system.
 The light beam angle can be 15° , 25° , 30° , 45° , 75° , optional.
 High speed electronic strobe reaches 1-18 times/second
 Size: 380 x 350 x 450 mm
 N/G Weight: 10.0/12.0kg

SM 108x3W



Voltage: AC 90V-240V
 Consumption: 350w
 Frequency: 50Hz-60Hz
 Lamp: 3W*108pcs high power LED
 1W108pcs (R:18,G:42,B:36,W:12)
 3W108pcs (R:18,G:36,B:36,W:18)
 100,000 hours lifetime, energy saving, LED
 Channel: 9CH/13CH/15CH can be choose
 Control mode: DMX/master-slave/voice
 Level scan: 540° or 630° (16 bit correct exact scan)
 Tilt scan: 265° (16 bit correct exact scan)
 Light degree: 15/25/45 can be choose
 Size: 350 *230 *450mm
 Packing Size: 420 *300 *390mm
 N.W: 8.8Kg
 G.W: 10.1Kg

SM 19 LED WASH



Voltage: AC 90-245V, 50-60Hz
 Light Source: 19*12W 4 in 1 Osram LED, extremely small, fast and powerful LED moving beam
 Lifespan: 10000hrs with low power consumption
 Motor: 2 phase motor
 Beam Angle: 8-45°
 Pan/Tilt: X axis 540°, Y axis 220° ,
 16bit fine-tuning
 Dimmer: 0-100% linear adjustment Strobe;
 Electronic strobe with pulse and random effects, 1-25tims/s
 Channel: 16CH Control
 Mode: DMX512, Sound active, Master-slave and Auto
 Display: LCD display with Chinese and English
 Function: With LED shutter, scan position memory and auto reposition. LED rainbow effect.
 Built-in programs with macro effects.
 Body Size: 325*188*395mm
 N.G/W: 8.5/10kgs

SM 19 LED ABEJA GRANDE



Voltage: 100-240V 50/60Hz
 Lamp Source : 19x15W Osram Ostar RGBW
 4-in-1 high brightness LEDs, 50,000 h.
 Color temperature : 2500 - 8000 k
 OPTICS : 4°-60° Electronic Zoom angle
 Effects Section: Three operating modes: wash, beam, FX (Kaleido effects) Front Lens Bi-directional Rotation
 Digital Wash-Beam Framing effect Beam edge softening control (in Wash mode) 0-100% linear electronic dimmer
 Adjustable speed stop/strobe effect, with instantaneous blackout Dedicated channel for color temperature setting
 RGBW auto-tuning
 DMX512: 3/5-pin XLR IN-OUT sockets
 Power connect: Powercon in&out
 MOVING BODY Movement by means of two stepper motors, controlled by microprocessor Automatic repositioning of PAN and TILT after accidental movement not controlled by control unit.
 Display: LCD display
 Travel: PAN = 540° TILT = 210°
 Dimension Size: 494*358*253
 Weight: 15 Kg

SM MATRIX 25X12



Voltage: AC90-240V, 50-60 Hz
 Lamp: 25pcs *12W 4 in 1 Led
 Lifespan: 100000H, low power consumption
 Pan: infinite+ 16 bit Tilt: infinite+ 16 bit
 Beam angle: 7 degree
 Channel: 19/29/117 choosable (factory default: 19)
 Dimming: 0-100% liner dimming
 Strobe: 1-25timesec high speed strobe
 Control Mode: DMX512, master-slave, sound, auto-run
 Display: Blue LCD Display
 Function: all dimming, scanning memory, auto-reset;
 every single lamp can be controled solely, all kinds of letter, number, gobo can be set; beam, wash, effect light.
 Applicable place: big show, upmarket bar, KTV, club etc.

SM 130



Voltage: AC110V-130V, 50-60HZ
 Light source: 10Wx4 led LIUMING lamp
 Power: 80W
 Channel: 9CH/28CH
 Control Mode: DMX512, auto-run, master-slave
 Product Size: 1010*250*100mm
 Packing Size: 1080*170*320mm
 N.W: 9.5KG
 G.W: 11.3KG

SM 121



Voltage: AC 220V/110V
 Frequency: 50-60Hz
 Power: 80W
 Led: 4-in-1 *7pcs led
 Channel: 4CH/8CH
 Control modes: sound control, auto-run, DMX521
 Function: can make magic, color mixed, charming effect
 N.W: 1.1kg
 G.W: 1.2kg
 Product Size: 180*170*220mm
 Packing Size: 210*140*230mm

SM 122



Voltage: AC 220V/110V
 Frequency: 50-60Hz
 Power: 70W
 Led: 3w*18pcs led
 Channel: 3CH/6CH
 Control modes: sound control, auto-run, DMX521
 Function: can make magic, color mixed, charming effect
 G.W: 1.5kg

SM 095



Voltage: AC90V-240V ,50/60HZ
 Consumption: 200W
 LED quantity: 18pcs 4 in 1 (RGBW 4 in 1 mix color)
 lens angel: 15,25,45degrees (optional)
 Display panel: Digital
 Control function: Standard DMX512, master-slave control, Auto.
 IP rate: IP65 DMX channel: 8CH
 Certification: CE, ROHS certification
 N.W : 7.3Kg Packing size: 260*270*320mm

SM 094



Voltage: AC90V-240V, 50/60HZ
 Consumption: 200W Power: 200W
 Lamp: 18pcs Led 4 in 1
 Dimming curve: 0-100% Linear dimming
 dim4Nonlinear dimmer (2930K)
 Strobe speed: 0-13Hz
 Color Temperature Range: 5m color temperature 1500 LX
 Color: RGBW Safety certificate: CE, ROHS
 N.W: 4Kg G.W: 4.5Kg
 Internal Packing Size: 255mm*255mm*380mm
 External Package size: 560mm*560mm*440mm (Carton 4in1)

SM 034



Voltage: AC90V-240V
Frequency: 50Hz-60Hz
Consumption: 120W
Lamp: 3W*36pcs LED lamp (R12、G12、B12)
Channel: 3CH/6CH can change
Function: DMX512 control, automatic, voice control
Can make magic, colour mixed, charming effect
N.W: 4kg G.W: 4.5Kg
Internal Packing Size: 250mm*250mm*360mm
External Package size: 560mm*560mm*440mm
(Carton 4in1)

SM 034F



Voltage: AC 90-240V 50/60Hz
Power: 120W
Lamp: 3W * 36pcs LED lamp (3 in 1, RGB)
Signal: DMX 512
Channel: 3 CH / 7 CH
Control mode: DMX, Master-Slave; Voice control, automatic
N.W: 4Kg G.W: 4.5Kg
Internal Packing Size: 255*255*380mm
External Package size: 560*560*440mm
(Carton 4 in 1)

SM 034D



Voltage: AC90V-240V
Frequency: 50-60Hz
Power: 120W
Lamp: 3W*36pcs LED lamp (R12、G12、B12)
Channel: 3CH/6CH can change
Operation mode: Voice control, automatic, DMX512
Function: Can compile, mixed color, charming dream effect
N.W: 2.5Kg G.W: 3Kg
size: 250mm*250mm*340mm
Package size: 250mm*250mm*360mm (Carton 4 in 1)

SM 046F



voltage: AD90-240 - v 50-60 hz power: 200 w
Lamp: 3 w * 54 lamp bead (triad RGB)
Lamp bead ratio: R54: B54: G54:
color: RGB color mixture system, 16.7 million
kinds of color changes
Beam Angle: 25° Alternative perspectives (15, 45)
Independent dimming move light: red, green and blue
Manual dimming macro adjustment
Stroboscopic: digital stroboscope 1-255 times per second
Control mode: international standard DMX512 signal,
3 core standard card nong interface
Number of channels: streamline pattern 3 channel,
Standard mode: 7 channels
Operation mode: single, online, controller mode
N.W: 4Kg G.W: 4.5Kg
Package size : 560mm*560mm*440mm (Carton 4 in 1)

SM 046B



Voltage: AC90V-240V Frequency: 50Hz-60Hz
Consumption: 180W
Lamp: 3W*54pcs LED lamp (R12, G18, B18, W6)
Channel: 4CH/8CH
Function: DMX512 control, automatic, voice control
Can make magic, colour mixed, charming effect
N.W: 2.5Kg G.W: 3Kg
Internal Packing Size: 250mm*230mm*340mm
External Packing Size: 250mm*250mm*360mm
(carton 4in1)

SM 047B



Voltage: AC90V-240V Frequency: 50Hz-60Hz
Consumption: 180W
Lamp: 3W*54pcs LED lamp (R12, G18, B18, W6)
Channel: 4CH/8CH IP rate: IP65
Function: DMX512 control, automatic, voice control
Can make magic, colour mixed, charming effect
N.W: 7.2Kg G.W: 7.7Kg
Internal Packing Size: 310*230*300mm
External Packing Size: 610*605*370mm
(carton 4 in 1) 33.3Kg

SM 065B



Voltage: AC90V-240V Frequency: 50/60Hz
Consumption: 250W
Lamp: 3W*72pcs (R14, G20, B20, W18)
Channel: Can be choose 4CH/8CH
Mode: DMX self track, voice control, master-slave
Function: electric dimmer from 0-100% (unchanged color)
high speed whitelight change color, strobe, can have
magic, mix-color effect.
Beam angel: can be choose 15° 25° 30° 45°
Packing size: 280 mm*230 mm*320mm
G.W: 2.8KG

SM 108 X 3W



Voltage: AC90V-240V Frequency: 50/60Hz
Consumption: 400W
Lamp: RGBW 3W*120pcs led lamp
Channel: 4CH/8CH
Mode: DMX, auto run, voice control, master-slave
Function: electric dimmer from 0-100%
(unchanged color) high speed white
light change color, strobe, can have
magic, mix-color effect.
Beam angel: can be choose 15° 25° 30° 45°
Packing size: 330 mm*270 mm*380mm
G.W: 6.6KG

SM 135



Voltage: AC90V~AC250V/50-60Hz
 Power: 300W
 Lamp: 3W*90pcs led (Can be customized waterproof)
 (R22, G22, B22, W24)
 CH: 4CH/8CH can change
 Control Model: DMX, Auto
 Master-Slave, automatic trigger, Voice
 Function: Electronic dimmer from 0-100% (unchangeable color)
 High speed white change color, strobe, can be magic mix color effect.
 Beam Angel: 15°/25°/30°/45° can be select
 Packing size: 280 mm*230 mm*320mm
 G.W: 6.5Kg

SM 050B



Voltage: AC90V-240V 50Hz / 60Hz
 Power: 120W
 Lamp: 3W*36pcs lamp
 Lamp angle : 15°/25°/ 45° (can choose)
 Control : 6CH DMX512 channel control
 G.W: 6.6Kg
 Package : 330 * 250 * 200 mm

SM 137



Voltage: AC110-240V, 50~60 Hz
 Lamp: 8pcs 10w high power RGBW led
 DMX Channel: 15/46 CH
 Movement: Pan/Tilt: X axis 540 degree,
 Y1 axis 120 degree, Y2 axis 120 degree
 Control mode: DMX512/Master-slave/Auto-run
 Display: Blue ground LCD display
 Beam angle: 3 degrees
 Pan/Tilt speed: 3 selectable for high,
 medium and low speed
 N.W: 9KG
 G.W: 11KG
 Product Size: 320*410*280mm
 Packing size: 510*380*380mm

SM 003



Voltage: AC110V/220V
 Power: 5000 w
 Frequency: 50 hz - 60 hz
 Light source: xenon bubble of 4000 w
 Color: 4 color + white light
 Range: 200 meters
 Manual adjust size of grating, manual cut light,
 Focus and aperture changes
 Gross weight: 120 kg
 Packing size: 2160 mm * 640 mm * 840 mm

SM 001



Voltage: AC110V / 220V
 Power: 3000W
 Frequency: 50 hz - 60 hz
 Channel: 4 ch
 Light source: HMI 2500 W
 Function: 4 color + white light, can be free to switch,
 Light circle size adjustable,
 Variable speed stroboscopic 1-10 times per second
 Gross weight: 50 kg
 Size: 1210 mm * 450 mm * 300 mm

SM 002A



Voltage: AC110V/220V
 Consumption: 1500W
 Frequency: 50Hz-60Hz
 Channels: 4 CH
 Lamp: HMI 1200W
 Function: 4 color +white, free for
 changing-over; iris adjustable;
 strobe: 1-10 times/ sec
 Packing size: 11200mm*410mm*280mm
 G.W: 50kg

SM 001



Can accommodate: more than 3000 species of lamp library files; More than 100 files; Movable external storage disk storage has more than 3000 kinds of new lamp library. The lamps and lanterns of choose way 2048 channels, 240 PCS lamps and lanterns, 240 Road dimmer control channel, 15 playback pusher, 450 can be controlled Memory, running lights or CUE list. MIDI/bass/alto, treble Voice control trigger contains standard VGA to output;
Product size: 750x600x150mm
Packing size: 810x680x280mm
Net weight: 20 Kg
gross weight: 39 kg

SM 015



DMX512/1990, Up to 1024 DMX channels, output with optical isolated.
Up to 80 intelligent Fixtures or 80 Dimmers can be controlled. Shape generator inside. Shape generator can create effects such as circles, spire, rainbow, etc
600 playbacks can be store as chase or scene.
Up to 600 steps can be store in chase.
LCD display with backlight.
12V accessory operate light (OPTIONAL)
Power: AC 100 240V / 50-60Hz
Size: 662 x 546 x 122mm

SM TIGER TOUCH



10 pageable playbacks, 60 pages
10 static playbacks – perfect for instant access
100% brighter 15.6" screen
Three metal shaft optical encoders offering luxurious precision
MIDI support for MIDI Notes and MIDI Timecode
Built in UPS (coming 2015)
4 physical DMX outputs, up to 16 over ArtNet or sACN - 8192 channels
Supports Titan Network Processors for DMX expansion up to 64 universes
Trigger inputs
Dual Ethernet port
Expand your control surface through wings, DMX In or MIDI
Dedicated cue stack control
Support for external touch screen
10 programmable executor buttons
Conveniently accessible front loading USB

SM 029



Voltage: AC110v/220V
Frequency: 50Hz-60Hz
Consumption: 30W
Lamp: F5*240pcs LED lamp
Channel: 4CH
Function: DMX512 control, automatic, voice control
N.W: 4.3Kg
G.W: 5.2Kg
Product size: 500*330*190mm
Packing size: 560*380*230mm

SM 099-099B



Voltage: AC110V-130V, 50-60HZ
Lamp: 10W*8pcs white (4 in 1 10W)
Power: 100W (120W)
Channel: 5CH/14CH
Function: Automatic, Master-Slave, DMX512
N.W: 6.4Kg G.W: 7.2Kg
Product size: 1080mm*130mm*210mm
Carton package: 1130mm*150mm*230mm

SM 112



Voltage: AC100-240v
Frequency: 50-60Hz
Lamp: 25pcs full color LED (white)
Lifespan: 50000hours
Color: RGB (warm white)
luminous flux: 1/4 Fresnel Lenses 3303lm/Diverging Lens 2994lm
Projection distance: 4-5 meters
Dimmer: 0 - 100% Linear dimming
Strobe: 0-25c
Function: super bright LED, energy saving; four digital tube display, power signals;
Conversion, automatic shutdown function; stand-alone/4 DMX/master-slave; auto-run; Fast concatenation design and convenient for multiple combinations; over-temperature protection
Place: television hall; Event; big show; theater etc.

SM 137B



Voltage: AC110-240V, 50~60 Hz
Lamp: 8pcs 10w high power RGBW led
DMX Channel: 15/46 CH
Movement: Pan/Tilt: X axis 540 degree, Y1 axis 120 degree, Y2 axis 120 degree
Control mode: DMX512/Master-slave/Auto-run
Display: Blue ground LCD display
Beam angle: 3 degrees
Pan/Tilt speed: 3 selectable for high, medium and low speed
N.W: 9KG
G.W: 11KG
Product Size: 320*410*280mm
Packing size: 510*380*380mm

SM 037



Laser type: DPSS laser
 Power: 20W
 Wave Length: 635NM/532NM
 Color: Red/Green
 Cooling: Air cooling
 Power of laser: R: 100mw/G: 30mw
 Motor: N1.8 High precision stepper motor
 Power Supply: 85-250V 50/60HZ
 Work mode: Voice control, Auto
 Suit Occasions: Disco, KTV, Bar, Night club
 and so on entertainment venues

SM 004



Voltage: AC110V/230V
 Frequency: 50-60Hz \pm 10%
 Power: 1500w
 Preheat time: 10 minutes
 Oil volume: 5KG
 Smoke distance: 15meters
 Smoke covered: 2500cu.ft/min
 Control mode: wire control, remote control
 Packing size: 530mm*300mm*280mm
 N.G: 5Kg
 G.W: 6.8Kg

SM 021



Power supply: AC 220V; Frequency: 50/60Hz
 Fuse Wire: 10A 250V
 Consumption Power: 1500w
 Warm-up time: About 10 minutes
 Smoke output: 10,000 cu.ft/min
 Tank Capacity: 2.5 Litre
 Equipping 24pcs high brightness LED light beads with 3 in 1 of RGB colors.
 Outputting the fog and the shiny LED in the same time, it will show colorful shining fog effect.
 Fog Timer: display in FM-8 and blue LCD. Including (setup interval time of outputting the fog and adjust the time of continuous outputting the fog)
 Size: 420mm*310mm*210mm
 N.W: 8.25kg

SM 005



Voltage: AC110V/230V
 Frequency: 50-60Hz \pm 10%
 Power: 1200w
 Preheat time: 10 minutes
 Oil volume: 3KG
 Smoke distance: 12meters
 Smoke covered: 2000cu.ft/min
 Control mode: wire control, remote control
 Packing size: 560mm*360mm*300mm
 G.W: 7kg



SONIDO MARTÍN SL.

POL. IND. LOS BURJEOS Nº10. C/LA FUENSANTA.

INFO@SONIDOMARTIN.COM

TLF: 607 96 02 11

DISTRIBUIDOR: